

Pneumatic Roller



Tru-Pac 915



Tru-Pac 915 Pneumatic Roller

Features include:

- 85 HP Kubota Engine
- Responsive Hydrostatic Drive
- Articulated Frame for Tru-tracking Compaction
- ROPS with Sunroof
- Suspension Operator's Seat
- Ballastable from 6.5 to 15 tons
- 100-gallon Pressurized Water Spray System
- All-wheel Oscillation
- Coco Mats with Spring-loaded Scrapers
- 11-Wheel Option

Designed with the Paving Professional in Mind.®

Specifications

Tru-Pac 915 Pneumatic Roller

DIMENSIONS	
Weight	13,500 lbs (6,124 kg)
Fully Ballasted Weight	30,500 lbs (13,835 kg)
Length	14'4" (4.37 m)
Body Width	72" (1.83 m)
Rolling Width	68" (1.73 m)
Height with ROPS	9'5" (2.87 m)
Height without ROPS	85" (2.16 m)
Wheelbase	100" (2.54 m)
Ground Clearance	11" (279 mm)
Inside Turning Radius	110" (2.79 m)
FRAME	
	Plate steel, welded throughout
ENGINE	
	85 HP @ 2,600 RPM (63 kw) Kubota
TRANSMISSION	
	Hydrostatic (no chain drive)
RUBBER TIRES	
Number of Tires	9
Size	7:50 x 15 (14-ply) smooth
Tire Overlap	1/2 inch (12.7 mm)
SPEED	
	0-15 mph (0-24 kph)
ARTICULATION/OSCILLATION	
Frame Articulation	+/- 39°
Frame Oscillation	+/- 10°
Tire Oscillation	+/- 4°
PRESSURIZED WATER SYSTEM	
Capacity	100 gallons (379 l)
FLUID CAPACITIES	
Hydraulic Reservoir	14 gallons (53 l)
Fuel	35 gallons (133 l)