

**JOB DONE RIGHT.**

**SWEEPMASTER  
400**



## **FEATURES**

- Shift-on-the-go for non-stationary gear shifts
- Single pivot broom design, clog-free pivot points
- VISTA Cab™ provides 43% more interior room & maximum operator visibility
- Forward and reverse foot pedal controls
- Easily adjusted broom down pressure
- Broom rotation 250 RPM
- Easy access to engine compartment
- Tow package or quick-disconnect push blade

Efficient, easy to maintain and street tough – LayMor's Sweepmaster 400 has got what it takes when it comes to your street, highway or interstate construction project. Count on LayMor Sweepmaster to get the job done right. Every time.

**STREET TOUGH.**

## KEY FEATURES

- Shift-on-the-go eliminates stopping the unit to shift to high gear.
- Available with tow package or quick-disconnect push blade.
- The single-point broom pivot design keeps the pivot point free of debris.
- Engine compartment designed for excellent airflow & easy access.
- Operator seat is behind the centerline of the broom for max visibility.
- Forward & reverse foot pedals free up hands for other operator functions.

## STANDARD EQUIPMENT & OPTIONS

- VISTA Cab™
  - Sprinkler system with tank selections: 180-gallons, low profile, easy water level view
  - 1/2 poly - 1/2 wire
  - Air conditioner & heater
  - Front windshield wiper/washer
  - Halogen high/low work lights
  - Turbo II pre-cleaner
  - Mirrors
  - Engine compartment doors
  - Rear windshield wiper/washer
  - Audible engine alarm and warning
  - High temp/low oil engine shutdown
  - Drum-type front brakes
  - ST 225/75R15 8-ply radial tires
  - LT 235/75R15 8-ply radial tires
  - 90" front-mounted material push blade
- OPTIONS:**
- All-steel brush
  - Canopy windshield
  - Suspension seat
  - 3" seat belt
  - Strobe
  - Rear work lights
  - Tachometer
  - Towing hitch package

## SPECIFICATIONS & DIMENSIONS

<b>ENGINE</b>	Kubota 3600 Tier 4i, 4 Cylinders	<b>MAX. TORQUE</b>	<b>215 FT-LBS @ 1600 RPM</b>
<b>DISPLACEMENT</b>	<b>199 CC</b>	<b>HORSEPOWER</b>	<b>74 @ 2600 RPM</b>
<b>WHEELBASE</b>	<b>11' 5.25"</b>	<b>TREAD WIDTH</b>	<b>5' 7"</b> (outside to outside)
<b>OVERALL HEIGHT</b>	<b>8' 9"</b> (to top of ROPS canopy)	<b>OVERALL LENGTH</b>	<b>15' 10"</b>
	<b>9' 4.5"</b> (to top of optional air conditioner)	<b>OVERALL WIDTH</b>	<b>8' 4"</b> (straight broom)
	<b>9' 9.5"</b> (to top of optional strobe light)		<b>7' 3.25"</b> (45° angle broom)
<b>CENTERLINE DISTANCE</b>	<b>2' 4"</b> (centerline of seat to centerline of broom)	<b>TURNING RADIUS</b>	<b>Outside: 21'</b> <b>Inside: 15' 4"</b>
<b>WEIGHT</b>	<b>5,660 lbs.</b> (with Cab) <b>4,600 lbs.</b> (with ROPS)		



**Streets**



**Highways**



**Interstates**



**Snow Removal**